

ENERGY RATINGS - CANADA

Window Style (Model)	Energy Rating (ER) Canadian Energy Star Program											
	Glass Options	ER	Energy Star Zone				SHGC	Visible Transmittance	Condensation Resistance	"U" Value	"U" Value	"R" Value
			A	B	C	D				(Metric)	(Imperial)	(Imperial)
										W/m ² -K	Btu/h/ft ² -°F	(Imperial)
3-Lite Single Slider Liftout #1374 CAN/CSA A440-00 Evaluation Report # 3186469TOR-002C 3Lite SLO Air - A3/Fixed Water - B3 Structural - C3 Forced Entry - F20	DUAL LITE											
	Clear – air – clear	18					0.60	0.63	48	2.56	0.45	2.22
	Clear – air – clear, grille	15					0.54	0.57	48	2.56	0.45	2.22
	Clear – air – LOF (3)	31	●	●	●		0.59	0.60	54	1.93	0.34	2.94
	Clear – air – LOF, grille	27	●	●			0.53	0.54	54	1.93	0.34	2.94
	Clear – argon – LOF (3)	35	●	●	●	●	0.59	0.60	57	1.76	0.31	3.23
	Clear – argon – LOF, grille	31	●	●	●		0.53	0.54	57	1.76	0.31	3.23
	Clear – argon/krypton – LOF (3)	35	●	●	●	●	0.59	0.60	57	1.76	0.31	3.23
	Clear – argon/krypton – LOF, grille	31	●	●	●		0.53	0.54	57	1.76	0.31	3.23
	Bronze – air – clear	12					0.49	0.48	44	2.56	0.45	2.22
	Bronze – air – clear, grille	9					0.44	0.43	44	2.56	0.45	2.22
	Bronze – argon – clear	14					0.49	0.48	46	2.44	0.43	2.33
	Bronze – argon – clear, grille	11					0.44	0.43	46	2.44	0.43	2.33
	Bronze – argon/krypton – clear	14					0.49	0.48	46	2.44	0.43	2.33
	Bronze – argon/krypton – clear, grille	11					0.44	0.43	46	2.44	0.43	2.33
	Bronze – air – LOF (3)	23	●				0.45	0.44	54	1.93	0.34	2.94
	Bronze – air – LOF, grille	20					0.40	0.39	54	1.93	0.34	2.94
	Bronze – argon – LOF (3)	27	●	●			0.45	0.44	57	1.76	0.31	3.23
	Bronze – argon – LOF, grille	24	●				0.40	0.39	57	1.76	0.31	3.23
	Bronze – argon/krypton – LOF (3)	27	●	●			0.45	0.44	57	1.76	0.31	3.23
	Bronze – argon/krypton – LOF, grille	24	●				0.40	0.39	57	1.76	0.31	3.23
	Grey – air – clear	11					0.47	0.43	44	2.56	0.45	2.22
	Grey – air –clear, grille	8					0.42	0.39	44	2.56	0.45	2.22
	Grey – argon – clear	13					0.47	0.43	46	2.44	0.43	2.33
	Grey – argon – clear, grille	10					0.42	0.39	46	2.44	0.43	2.33
	Grey – argon/krypton – clear	13					0.47	0.43	46	2.44	0.43	2.33
	Grey – argon/krypton – clear, grille	10					0.42	0.39	46	2.44	0.43	2.33
	Grey – air – LOF (3)	22	●				0.43	0.40	54	1.93	0.34	2.94
	Grey – air – LOF, grille	19					0.38	0.36	54	1.93	0.34	2.94
	Grey – argon – LOF (3)	25	●	●			0.43	0.40	57	1.76	0.31	3.23
	Grey – argon – LOF, grille	23	●				0.38	0.36	57	1.76	0.31	3.23
	Grey – argon/krypton – LOF (3)	25	●	●			0.43	0.40	57	1.76	0.31	3.23
	Grey – argon/krypton – LOF, grille	23	●				0.38	0.36	57	1.76	0.31	3.23
	366 – air – clear (2)	13	●				0.22	0.50	57	1.76	0.31	3.23
	366 – air – clear, grille	12					0.20	0.45	57	1.76	0.31	3.23
	366 – argon – clear (2)	18	●	●			0.21	0.50	60	1.53	0.27	3.70
	366 – argon – clear, grille	17	●	●			0.19	0.45	60	1.53	0.27	3.70
	366 – argon/krypton – clear (2)	18	●	●			0.21	0.50	60	1.53	0.27	3.70
	366 – argon/krypton – clear, grille	17	●	●			0.19	0.45	60	1.53	0.27	3.70

ENERGY RATINGS - CANADA

Window Style (Model)	Energy Rating (ER) Canadian Energy Star Program											
	Glass Options	ER	Energy Star Zone				SHGC	Visible Transmittance	Condensation Resistance	"U" Value	"U" Value	"R" Value
			A	B	C	D				(Metric)	(Imperial)	(Imperial)
										W/m ² ·K	Btu/h/ft ² ·°F	
3-Lite Single Slider Liftout #1374 CAN/CSA A440-00 Evaluation Report # 3186469TOR-002C 3Lite SLO Air - A3/Fixed Water - B3 Structural - C3 Forced Entry - F20	TRIPLE LITE											
	Clear – argon – clear – argon – LOF (5)	33	●	●	●		0.54	0.55	59	1.70	0.30	3.33
	Clear – argon – LOF – argon – LOF (3&5)	36	●	●	●	●	0.51	0.52	62	1.48	0.26	3.85
	Clear – argon/krypton – clear – argon/krypton – LOF (5)	34	●	●	●	●	0.54	0.55	60	1.65	0.29	3.45
	Clear – argon/krypton – LOF – argon/krypton – LOF (3&5)	36	●	●	●	●	0.51	0.52	63	1.48	0.26	3.85
	Clear – krypton – clear – krypton – LOF (5)	39	●	●	●	●	0.54	0.55	63	1.42	0.25	4.00
	Clear – krypton – LOF – krypton – LOF (3&5)	41	●	●	●	●	0.51	0.52	67	1.25	0.22	4.55
	Bronze – argon – clear – argon – clear	22	●				0.44	0.44	55	1.93	0.34	2.94
	Bronze – argon/krypton – clear – argon/krypton – clear	22	●				0.44	0.44	56	1.93	0.34	2.94
	Bronze – krypton – clear – krypton – clear	25	●	●			0.43	0.44	59	1.76	0.31	3.23
	Bronze – argon – clear – argon – LOF (5)	26	●	●			0.40	0.40	59	1.65	0.29	3.45
	Bronze – argon/krypton – clear – argon/krypton – LOF (5)	26	●	●			0.40	0.40	59	1.65	0.29	3.45
	Bronze – krypton – clear – krypton – LOF (5)	31	●	●	●		0.40	0.40	63	1.42	0.25	4.00
	Bronze – argon – LOF – argon – LOF (3&5)	28	●	●			0.37	0.37	61	1.48	0.26	3.85
	Bronze – argon/krypton – LOF – argon/krypton – LOF (3&5)	28	●	●			0.37	0.37	62	1.48	0.26	3.85
	Bronze – krypton – LOF – krypton – LOF (3&5)	33	●	●	●		0.37	0.37	65	1.25	0.22	4.55
	Grey – argon – clear – argon – clear	21	●				0.42	0.40	55	1.93	0.34	2.94
	Grey – argon/krypton – clear – argon/krypton – clear	21	●				0.42	0.40	56	1.93	0.34	2.94
	Grey – krypton – clear – krypton – clear	24	●				0.41	0.40	59	1.76	0.31	3.23
	Grey – argon – clear – argon – LOF (5)	25	●	●			0.38	0.36	59	1.65	0.29	3.45
	Grey – argon/krypton – clear – argon/krypton – LOF (5)	25	●	●			0.38	0.36	59	1.65	0.29	3.45
	Grey – krypton – clear – krypton – LOF (5)	30	●	●	●		0.38	0.36	63	1.42	0.25	4.00
	Grey – argon – LOF – argon – LOF (3&5)	28	●	●			0.36	0.34	61	1.48	0.26	3.85
	Grey – argon/krypton – LOF – argon/krypton – LOF (3&5)	28	●	●			0.36	0.34	62	1.48	0.26	3.85
	Grey – krypton – LOF – krypton – LOF (3&5)	32	●	●	●		0.35	0.34	65	1.25	0.22	4.55
	366 – argon – clear – argon – clear (2)	16	●				0.20	0.46	61	1.59	0.28	3.57
	366 – argon/krypton – clear – argon/krypton – clear (2)	17	●	●			0.20	0.46	61	1.53	0.27	3.70
	366 – krypton – clear – krypton – clear (2)	22	●	●	●		0.20	0.46	65	1.31	0.23	4.35